

Boomlift / Manlift

Used Boom Lift Garden Grove - One of the commonest types of industrial equipment and aerial equipment is the boom lift. Boom lifts go by numerous names including cherry pickers, elevating work platforms, aerial platforms, aerial devices and mobile elevating work platforms; created to conduct jobs at higher elevations. There are many places to find boom lifts at work including warehouses, contractors, various companies and in retail stores. Staying safe while working at high altitude is essential for daily success. There is a wide variety of boom lift models to choose from. A single operator can control a variety of boom lift models. Boom lifts are beloved in the agricultural and orchard industries, used to harvest fruit without requiring a separate ladder, they keep workers much safer since there is not climbing or bucket balancing involved. Ladders need to be secured on solid, even ground in order to be safely accessible, making them hard to rely on in a natural orchard setting. Boom lifts make it much easier to reach high tree tops for collecting fruit. Gaining Access Over Obstacles Certain boom lifts are designed to move up and over items. This makes working over obstacles possible This equipment is used in numerous industries including installing telephone poles and lines, maintaining overhead cables and window cleaning applications due to their ability to reach items when it is not practical to situate the machine directly underneath the issue. With a variety of joints allowing the machine to bend over or under items, the articulated boom lift is helpful for numerous applications. To enable operators to access many places, these sections of the boom lift can move independently. Famous for their tight turning radius, articulated booms offer an ideal solution for narrow hallways and storage facilities. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts These boom lifts are popular for numerous construction and maintenance jobs. They provide a vital piece to the fleet for servicing power lines and overhead wires. Certain models are outfitted with water cannons to be used in firefighting applications. Some models are built for extended reach applications and outfitted with telescoping sections. Certain articulating boom lifts can extend an additional six feet in any direction thanks to the additional jib in their design. The nickname "spiders" has been given to these boom lifts due to their legs which can support the machine on rough or steep terrain. Smaller units called interior articulating boom lifts are capable of fitting through doorways, making them valuable in retail, warehousing and storage facilities. Interior models are typically electric boom lifts due to their lack of dangerous carbon monoxide exhaust and quieter features. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These models extend upwards and outwards, relying on hydraulics that extend and retract. The operator who is situated in the platform has the controls to operate and extend the lift on their own. Certain larger and taller models feature a jib located close to the top similar to an articulating boom lift model. There are models on the market capable of reaching over 180 feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Available in 4WD and the ability to fit through small spaces. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Certain boom lift models have a jib or an extension located between the platform and the end of the main boom. This design facilitates an extra hinge or articulation point to enable the platform to move up and down or horizontally. Jibs are available on telescoping boom lifts and articulating boom lifts. Articulating boom lifts have a joint found approximately halfway between the platform and the wheels to allow it to reach over obstacles. The operator can lower the machine again afterward if required. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. The first articulating Genie Z-30/20 boom was launched in 1985. These machines became immediately popular with their up-andover design that continues to make them sought after nowadays. Proper Safety Measures Of course, safety is the highest priority when operating any type of boom lift. Safety hazards must be advertised to everyone who is working in the area for best practices. Operating the equipment safely is vital for the operator and everyone in the vicinity. Before operating the machine, effective communication and essential safety gear need to be in place. Ensure there are no flammable or combustible items, open flame or lit cigarettes near the machine, engine fuels or battery gases. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. Keep work surfaces and charging stations clean and free from clutter or tools that could puncture the tires or damage the machine or its components. Daily Maintenance Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. Stabilizing the weight is accomplished supportive devices to lift and distribute the load. Chains, fasteners and straps need to be inspected regularly to ensure they are in optimum condition. Single-use fasteners and components must not be reused as they may fail and become extremely dangerous. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Adequate ventilation and lighting are essential in garages, workshops and along workbenches. To organize and specify, maintenance is categorized into a variety of subsections including Annual Maintenance, Quarterly Maintenance, Programmed and Commissioning Maintenance Intervals. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Not complying with routine maintenance can put the operator at a huge safety risk, lead to damaged components, terrible performance and preventable downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. The term commissioning refers to a list of single maintenance procedures that need to be completed at 50- and 150-hour intervals to keep the machine optimally running. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. Maintenance procedures are based on the operating hours of the boom lift and programmed maintenance may be conducted during pre-delivery machine preparation. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.